




# 1967-72 Chevrolet Pickup

Control Panel Kit

(473080)

(473081)



18865 Goll St. San Antonio, TX 78266

Phone: 800-862-6658

Sales: [sales@vintageair.com](mailto:sales@vintageair.com)

Tech Support: [tech@vintageair.com](mailto:tech@vintageair.com)

[www.vintageair.com](http://www.vintageair.com)



[www.vintageair.com](http://www.vintageair.com)

# Table of Contents

Cover.....	1
Table of Contents.....	2
Packing List (Machined Finish)/Parts Disclaimer.....	3
Packing List (Black Anodized)/Parts Disclaimer.....	4
OEM Control Panel Removal.....	5
Control Panel Installation.....	6
Control Panel Calibration Procedure.....	7
Control Panel Calibration Procedure (Cont.).....	8
Gen IV Wiring Diagram.....	9
Gen 5 Wiring Diagram.....	10
Operation of Controls.....	11
Packing List (Machined Finish).....	12
Packing List (Black Anodized).....	13




www.vintageair.com

## Packing List: (473080) Machined Finish Control Panel

No.	Qty.	Part No.	Description
1.	1	473080	Control Panel Assembly, Machined Finish
2.	1	232007-VUR	Control Harness, Gen IV/Gen 5 Universal
3.	2	180031	Nut, 5/16-18, Hex
4.	2	180030	Screw, 5/16-18 x 1/2", Pan Head
5.	1	231520	Ground Wire

**\*\* Before beginning installation, open all packages and check contents of shipment.  
Please report any shortages directly to Vintage Air within 15 days. After 15 days,  
Vintage Air will not be responsible for missing or damaged items.**



**NOTE: Images may not depict actual parts and quantities.  
Refer to packing list for actual parts and quantities.**






www.vintageair.com

## Packing List: (473081) Black Anodized Control Panel

No.	Qty.	Part No.	Description
1.	1	473081	Control Panel Assembly, Black Anodized
2.	1	232007-VUR	Control Harness, Gen IV/Gen 5 Universal
3.	2	180031	Nut, 5/16-18, Hex
4.	2	180030	Screw, 5/16-18 x 1/2", Pan Head
5.	1	231520	Ground Wire

**\*\* Before beginning installation, open all packages and check contents of shipment.  
Please report any shortages directly to Vintage Air within 15 days. After 15 days,  
Vintage Air will not be responsible for missing or damaged items.**



**NOTE: Images may not depict actual parts and quantities.  
Refer to packing list for actual parts and quantities.**



www.vintageair.com

## OEM Control Panel Removal

1. Remove the (2) OEM screws from under the dash (See Figure 1, below).
2. Disconnect the cables and wires from the back of the control panel.
3. Remove the control panel from the dash.




Figure 1



www.vintageair.com

## Control Panel Installation

1. From behind the dash, place the control panel against the dash opening (See Figure 1, below).
2. While pressing the bezel firmly into the dash aperture, secure the control panel to the dash using (2) 5/16-18 x 1/2" pan head screws and (2) 5/16-18 hex nuts (See Figure 1, below).
3. Plug the control harness into the back of the control panel as shown in Figure 2, below.
4. Plug the control harness into the ECU module on the sub case as shown in Figure 3, below.




Figure 1




Figure 2

**NOTE:** When using a Vintage Air supplied control panel, connect the Tan 20 AWG wire from the Gen IV wiring harness (232010) or the Gen 5 wiring harness (231505) to the factory dash lights to enable panel backlighting.




Figure 3



[www.vintageair.com](http://www.vintageair.com)

## ***Control Panel Calibration Procedure***

On Vintage Air Gen IV and Gen 5 systems using cable converters or replacement electronic controls, it is necessary to calibrate the system to your specific control panel. This procedure ensures that the travel of your control panel levers or knobs is translated into precise control of the blower speed, temperature blend and mode door position. Please carefully read and understand these procedures before beginning. The procedure may be repeated as many times as necessary to get it right.

### **Gen IV Systems:**

In preparation for calibration, you will need to attach the supplied white ground jumper wire (PN 231520) to a suitable chassis ground. This jumper wire must be easily connected to the gray programming wire located in the main Gen IV wiring harness next to the compressor relay. During the calibration procedure, you will connect the white jumper to the gray program wire, which will "teach" the Gen IV ECU the upper limits of the control levers or knobs. The blower will momentarily change speeds, signaling that the upper limits have been "learned". You will move the levers or knobs to opposite extreme positions of their travel and then disconnect the white jumper. The blower will pulse on/off, signaling that the lower limits have been learned and that the calibration procedure is complete.

### **Gen 5 Systems:**


In preparation for calibration, you will need to attach the supplied white ground jumper wire (PN 231520) to a suitable chassis ground. This jumper wire must be easily connected to the gray programming wire located in the main Gen 5 wiring harness, see the Gen 5 wiring diagram and instructions for more information. During the calibration procedure, you will connect the white jumper to the gray program wire, and ground, which will then put the ECU into calibration mode. When the ECU is in calibration mode, the blower will default to medium speed and the ECU will flash a solid red light. Once in calibration mode you will cycle the controls as indicated in the calibration procedure on the next page. When complete, the jumper and program wire will be disconnected. The blower will turn off indicating calibration is complete.



www.vintageair.com

## Control Panel Calibration Procedure (Cont.)

1. Turn on the ignition switch (Do not start the engine).



2. Move the control levers/knobs to the positions shown.




3. Connect the white jumper wire to the gray program wire. Wait approximately 5 seconds for the blower speed to change if using a Gen IV system, if using a Gen 5 system wait for the blower to default to medium speed.



4. Move the control levers/knobs to the positions shown.




5. Disconnect the white jumper wire from the gray program wire. The blower speed will change if using a Gen IV system, and will shut off if using a Gen 5 system, indicating completion of the calibration procedure.



6. Confirm proper operation of controls. Repeat procedure if necessary. When finished, tape over program wire connector with electrical tape to prevent accidental contact with chassis ground.




232007-VUR




VIEWED FROM WIRE SIDE


## 232002-VUA




VIEWED FROM

## PROGRAM



NOTE:  = CHASSIS GROUND

## GEN IV ECU




- \* Dash lamp is used only with type 232007-VUR harness.
- \*\* **Warning:** Always mount circuit breaker as close to the battery as possible. (NOTE: Wire between battery and circuit breaker is unprotected and should be carefully routed to avoid a short circuit).
- \*\*\* Wide open throttle switch contacts close only at full throttle, which disables A/C compressor.



www.vintageair.com

## Gen 5 Wiring Diagram



\* Dash lamp (TAN wire) is used only with type 232007-VUR harness.

\*\* Wide open throttle switch contacts close only at full throttle, which disables A/C compressor.

\*\*\* Install fuse assemblies at or as near to the battery as possible.



www.vintageair.com

## Operation of Controls

On Gen IV or Gen 5 systems with three lever/knob controls, the temperature control toggles between heat and A/C operations. To activate A/C, move the temperature lever/knob all the way to cold and then back it off to the desired vent temperature. For heat operation, move the temperature lever/knob all the way to hot and then adjust to the desired vent temperature. The blower will momentarily change speed, each time you toggle in and out of heat and A/C operations, to indicate the change. **NOTE: For proper control panel function, refer to Pages 7 and 8 for calibration procedure.**

### Blower Speed


This lever/knob controls blower speed, from OFF to HI.

### Mode Control

This lever/knob controls the mode positions, from DASH to FLOOR to DEFROST, with a blend in between.

### Temperature Control

This lever/knob controls the temperature, from HOT to COLD.



## A/C Operation

### Blower Speed

Adjust to desired speed.

### Mode Control

Adjust to desired mode position (DASH position recommended).

### Temperature Control

For A/C operation, adjust to coldest position to engage compressor (Adjust between HOT and COLD to reach desired temperature).



## Heat Operation

### Blower Speed

Adjust to desired speed.

### Mode Control

Adjust to desired mode position (FLOOR position recommended).

### Temperature Control

For maximum heating, adjust to hottest position (Adjust between HOT and COLD to reach desired temperature).



## Defrost/De-fog Operation

### Blower Speed

Adjust to desired speed.

### Temperature Control

Adjust to desired temperature.

### Mode Control

Adjust to DEFROST position for maximum defrost, or between FLOOR and DEFROST positions for a bi-level blend (Compressor is automatically engaged).










www.vintageair.com

## Packing List: (473080) Machined Finish Control Panel

No.	Qty.	Part No.	Description	
1.	1	473080	Control Panel Assembly, Machined Finish	_____
2.	1	232007-VUR	Control Harness, Gen IV/Gen 5 Universal	_____
3.	2	180031	Nut, 5/16-18, Hex	_____
4.	2	180030	Screw, 5/16-18 x 1/2", Pan Head	_____
5.	1	231520	Ground Wire	_____

Checked By: \_\_\_\_\_  
Packed By: \_\_\_\_\_  
Date: \_\_\_\_\_



NOTE: Images may not depict actual parts and quantities.  
Refer to packing list for actual parts and quantities.




www.vintageair.com

## Packing List: (473081) Black Anodized Control Panel

No.	Qty.	Part No.	Description	
1.	1	473081	Control Panel Assembly, Black Anodized	_____
2.	1	232007-VUR	Control Harness, Gen IV/Gen 5 Universal	_____
3.	2	180031	Nut, 5/16-18, Hex	_____
4.	2	180030	Screw, 5/16-18 x 1/2", Pan Head	_____
5.	1	231520	Ground Wire	_____

Checked By: \_\_\_\_\_  
Packed By: \_\_\_\_\_  
Date: \_\_\_\_\_



NOTE: Images may not depict actual parts and quantities.  
Refer to packing list for actual parts and quantities.